

Bearing No. K12X15X10H



Fw	12 mm
Ew	15 mm
Bc	10 mm
Cr	5.85
Cu	1.15
P/S	S
C0r	7.51
Noun	Bearing
Bore	0.472 Inch 12 Millimeter
Width	0.394 Inch 10 Millimeter
UNSPSC	31171512
Weight	0.003 Kg
Retainer	Yes
Oil lub.	37000
Category	Needle Non Thrust Roller Bearing
Inventory	0.0
Separable	No
Component	Roller Assembly Only
Enclosure	Not Applicable
Closed End	Not Applicable
Grease lub.	24000
Bearing No.	K12X15X10H
Shaft(max.)	12.000
Shaft(min.)	11.992
Weight / LBS	0.007
Housing(max.)	15.017
Housing(min.)	15.006
Inch - Metric	Metric

Product Group	B04144
Self Aligning	No
Other Features	Radial Roller Hardened Steel Cage
Bearing number	K12X15X10H
Keyword String	Needle
Thrust Bearing	No
Rolling Element	Needle Roller Bearing
Outside Diameter	0.591 Inch 15 Millimeter
Long Description	12MM Bore; 15MM Outside Diameter; 10MM Width; Needle Roller Bearing; Roller Assembly Only; No Self Aligning; Retainer; Single Row of Rollers; No Separable
Manufacturer URL	http://www.koyousa.com
(Refer.)Mass(kg)	0.003
Manufacturer Name	KOYO
Weight / Kilogram	0.008
Bore Diameter (mm)	12
Outer Diameter (mm)	15
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.40.00.00
(Oil) Lubrication Speed	37000 r/min
Manufacturer Item Number	K12X15X10H
Number of Rows of Rollers	Single Row
(Grease) Lubrication Speed	24000 r/min
Basic static load rating (C0)	7.51 kN
Basic dynamic load	5.85 kN

rating (C)	
------------	--