



Bearing No. YSA 212-2FK + H 2312

| | |
|-------------------------------------|----------------------|
| C | 26 mm |
| d | 55 mm |
| D | 110 mm |
| B | 42.5 mm |
| Size (mm) | 110x55x62 |
| Width (mm) | 62 |
| d ₃ | 80 mm |
| B ₁ | 62 mm |
| s ₁ | 33.8 mm |
| d ₃ | 80 mm |
| d ₂ | 75.64 mm |
| B ₁ | 62 mm |
| d ₁ | 55 mm |
| Limiting speed | 3400 r/min |
| Bearing number | YSA 212-2FK + H 2312 |
| s ₁ - ? | 33.8 mm |
| Associated spanner | HN 12-13 |
| Bore Diameter (mm) | 110 |
| Outer Diameter (mm) | 55 |
| d ₁ ? | 75.64 mm |
| Limiting speed ¹⁾ | 3400 r/min |
| Basic dynamic load rating C | 52.7 kN |
| Basic dynamic load rating - C | 52.7 kN |
| Mass bearing + adapter sleeve | 1.55 kg |
| Calculation factor f ₀ | 14 |
| Fatigue load limit P _u | 1.53 kN |
| Fatigue load limit - P _u | 1.5 kN |
| | |

| | |
|--|-------|
| Calculation factor - f_0 | 14 |
| Basic static load rating C_0 | 36 kN |
| Basic static load rating - C_0 | 36 kN |
| Recommended lock nut tightening angle ? | 95 ° |