



Bearing No. NKX15-Z

	IR12X15X16 / Suitable inner ring
D	24 mm
m	47 g / Weight
Noun	Bearing
Banded	No
Bore 1	0.591 Inch 15 Millimeter
UNSPSC	31171537
Height	0.906 Inch 23 Millimeter
Bore 2	0.591 Inch 15 Millimeter
Category	Thrust Roller Bearings
Size (mm)	15x24x23
Inventory	0.0
Width (mm)	23
Weight / LBS	0.097
d_w	15 mm / Tolerance: E8
d_a	23,7 mm
Inch - Metric	Metric
C_2	6,5 mm
C_r	12100 N / Dynamic load rating (radial)
F_w	15 mm
Self Aligning	No
Product Group	B00234
n_G	9500 1/min / Limiting speed
Cage Material	Steel
C_a	10500 N / Dynamic load

	rating (axial)
Thrust Bearing	Yes
Bearing number	NKX15-Z
Keyword String	Combination
C_{ua}	810 N / Fatigue limit load, axial
C_{ur}	2320 N / Fatigue limit load, radial
C_{0a}	16800 N / Static load rating (axial)
C_{0r}	12700 N / Static load rating (radial)
Other Features	With Grease Retaining Cap
Rolling Element	Combination - Needle Roller and Thrust Ball Bearing
r_{min}	0,3 mm
Precision Class	ABEC 1 ISO P0
Long Description	15MM Bore 1; 15MM Bore 2; 24MM Outside Diameter; 23MM Height; Combination - Needle Roller and Thrust Ball Bearing; Single Direction; Not Self Aligning; Not Banded; Steel Cage; ABEC 1 ISO P0; Roller
Manufacturer URL	http://www.ina.com
Outside Diameter	0.945 Inch 24 Millimeter
Manufacturer Name	SCHAEFFLER GROUP
Weight / Kilogram	0.056
$r_{a\ max}$	0,3 mm
$D_{2\ max}$	29,2 mm
Bore Diameter (mm)	15

Outer Diameter (mm)	24
Minimum Buy Quantity	N/A
Component Description	Roller Assembly plus Raceways
Harmonized Tariff Code	8482.80.00.40
Manufacturer Item Number	NKX15Z
Single or Double Direction	Single Direction
C - 23 mm / Tolerance: -0,25	23 mm / Tolerance: 0,25
Overall Height with Aligning Washer	0 Inch 0 Millimeter
C ₁ - 9 mm / Tolerance: -0,2	9 mm / Tolerance: 0,2