



Bearing No. NKX15T2

k	2.5 mm
d	15 mm
D	24 mm
C	23 mm
Cr	8.25 kN
dw	15 mm
Fw	15 mm
D1	28 mm
C1	9 mm
Dw	2 mm
Ca	10.5 kN
C2	6,5 mm
Lw	9.8 mm
Dw1	4.76 mm
C0r	10.2 kN
C0a	16.8 kN
Mass	0.04 kg
Weight	0,044 Kg
da min	23 mm
r min.	0,3 mm
rs min	0.3 mm
ras max	0.3 mm
series:	NKX
ra max.	0,3 mm
da min.	23 mm
flanges:	No Flange
Category	Roller Bearings
Inventory	0.0
Nlim (oil)	8,800 rpm
maximum rpm:	8800 RPM

Product Group	B04144
closure type:	Open
Nlim (grease)	6,200 rpm
bore diameter:	15 mm
overall width:	23 mm
Bearing number	NKX15T2
Precision class	P0
precision rating:	Not Rated
Weight / Kilogram	0.047
outside diameter:	28 mm
Manufacturer Name	NTN
Bore Diameter (mm)	15
Outer Diameter (mm)	28
Minimum Buy Quantity	N/A
needle bearing type:	Machined Bearing with No Inner Ring
static load capacity:	1040 kgf
lubrication hole type:	No Hole
dynamic load capacity:	840 kgf
(Grease) Lubrication Speed	6200 r/min
Static load rating axial (C0)	16,8 kN
Dynamic load rating axial (C)	10,5 kN
Lubrication hole on outer ring	Oui/Yes
Static load rating radial (C0)	10,2 kN
Dynamic load rating radial (C)	8,25 kN
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C

