



Bearing No. NKX17-Z

	IR14X17X17 / Suitable inner ring
m	55 g / Weight
D	26 mm
Noun	Bearing
UNSPSC	31171537
Banded	No
Height	0.984 Inch 25 Millimeter
Bore 2	0.669 Inch 17 Millimeter
Bore 1	0.669 Inch 17 Millimeter
Category	Thrust Roller Bearings
Size (mm)	17x26x25
Inventory	0.0
Width (mm)	25
Weight / LBS	0.117
C_a	10800 N / Dynamic load rating (axial)
n_G	8500 1/min / Limiting speed
Cage Material	Steel
Inch - Metric	Metric
C_r	13500 N / Dynamic load rating (radial)
Product Group	B00234
d_w	17 mm / Tolerance: E8
d_a	25,7 mm
C_2	8 mm
F_w	17 mm

Self Aligning	No
Other Features	With Grease Retaining Cap
Thrust Bearing	Yes
Keyword String	Combination
Bearing number	NKX17-Z
C_{ur}	2750 N / Fatigue limit load, radial
C_{ua}	870 N / Fatigue limit load, axial
C_{0a}	18200 N / Static load rating (axial)
C_{0r}	15000 N / Static load rating (radial)
Rolling Element	Combination - Needle Roller and Thrust Ball Bearing
Precision Class	ABEC 1 ISO P0
r_{min}	0,3 mm
Outside Diameter	1.024 Inch 26 Millimeter
Manufacturer URL	http://www.ina.com
Long Description	17MM Bore 1; 17MM Bore 2; 26MM Outside Diameter; 25MM Height; Combination - Needle Roller and Thrust Ball Bearing; Single Direction; Not Self Aligning; Not Banded; Steel Cage; ABEC 1 ISO P0; Roller
Weight / Kilogram	0.066
$D_{2\ max}$	31,2 mm
$r_{a\ max}$	0,3 mm
Manufacturer Name	SCHAEFFLER GROUP
Bore Diameter (mm)	17

Outer Diameter (mm)	26
Minimum Buy Quantity	N/A
Component Description	Roller Assembly plus Raceways
Harmonized Tariff Code	8482.80.00.40
Manufacturer Item Number	NKX17Z
Single or Double Direction	Single Direction
C - 25 mm / Tolerance: -0,25	25 mm / Tolerance: 0,25
Overall Height with Aligning Washer	0 Inch 0 Millimeter
C ₁ - 9 mm / Tolerance: -0,2	9 mm / Tolerance: 0,2