



Bearing No. 61802-2RS1

| | |
|---------------|----------------------------|
| D | 24 mm |
| d | 15 mm |
| B | 5 mm |
| C | 5 mm |
| D1 | 22,2 mm |
| D2 | 0,3 mm |
| d1 | 17,8 mm |
| d2 | - mm |
| Bore | 0.591 Inch 15 Millimeter |
| Noun | Bearing |
| UNSPSC | 31171504 |
| Weight | 0,0074 Kg |
| r2 min. | 17 mm |
| r1 min. | 17 mm |
| da min. | 17,8 mm |
| Da max. | 22 mm |
| ra max. | 0,3 mm |
| series: | 61 |
| Category | Single Row Ball Bearing |
| Inventory | 8.0 |
| Size (mm) | 15x24x5 |
| Snap Ring | No |
| Enclosure | 2 Seals |
| Width (mm) | 5 |
| bore type: | Round |
| Weight / LBS | 0.02 |
| Mass bearing | 0.0074 kg |
| maximum rpm: | 17000 RPM |
| Product Group | B00308 |
| | |

| | |
|---------------------|---|
| closure type: | Double Sealed |
| Cage Material | Steel |
| Inch - Metric | Metric |
| bore diameter: | 15 mm |
| overall width: | 5 mm |
| Keyword String | Ball |
| cage material: | Steel |
| fillet radius: | 0.3 mm |
| Bearing number | 61802-2RS1 |
| Enclosure Type | Contact Seal |
| Limiting speed | 17000 r/min |
| Reference speed | – r/min |
| Rolling Element | Ball Bearing |
| finish/coating: | Uncoated |
| Precision Class | ABEC 1 ISO P0 |
| Outside Diameter | 0.945 Inch 24 Millimeter |
| Outer Race Width | 0.197 Inch 5 Millimeter |
| Long Description | 15MM Bore; 24MM Outside Diameter; 5MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Manufacturer URL | http://www.skf.com |
| Manufacturer Name | SKF |
| Weight / Kilogram | 0.009 |
| outside diameter: | 24 mm |
| precision rating: | Not Rated |
| outer ring width: | 5 mm |
| Bore Diameter (mm) | 15 |
| Internal Clearance | C0-Medium |
| d _a max. | 17.8 mm |

| | |
|--------------------------------------|--------------------------|
| d _a min. | 17 mm |
| r _a max. | 0.3 mm |
| D _a max. | 22 mm |
| Outer Diameter (mm) | 24 |
| internal clearance: | C0 |
| r _{1,2} min. | 0.3 mm |
| Minimum Buy Quantity | N/A |
| d ₁ ? | 17.8 mm |
| d ₂ ? | 0 mm |
| D ₂ ? | 0 mm |
| row type & fill slot: | Single Row Non-Fill Slot |
| static load capacity: | 1.1 kN |
| Harmonized Tariff Code | 8482.10.50.68 |
| dynamic load capacity: | 1.9 kN |
| Calculation factor (f ₀) | 14 |
| Fatigue load limit (P _u) | 0,048 |
| Manufacturer Item Number | 61802 2RS1 |
| Internal Special Features | No |
| Basic dynamic load rating C | 1.9 kN |
| operating temperature range: | -40 to +210 °F |
| Basic dynamic load rating (C) | 1,9 kN |
| Basic static load rating (C0) | 1,1 kN |
| Maximum Capacity / Filling Slot | No |
| Fatigue load limit P _u | 0.048 kN |
| Calculation factor k _r | 0.015 |
| Calculation factor f ₀ | 13.8 |
| Basic static load rating | 1.1 kN |

| | |
|----------------|--|
| C ₀ | |
|----------------|--|