



Bearing No. 16012

D	95 mm
d	60 mm
B	11 mm
C	11 mm
r	0.6
Z_	17
B_	11
D_	95
ra	0.6
C0	17.5
fo	16.3
DI_	69.562
SRE	4.11
SRI	4.11
D_a	91
DA_	7.938
DE_	85.438
mass	0.281
SREN	-0.02
SBRG	0
KBRG	6101
SREX	0.02
Bore	2.362 Inch 60 Millimeter
SRIX	0.02
Noun	Bearing
SRIN	-0.02
yobi	16012
SDM_	77.5
bomp	0

C_conv	20000
da min	64
LangID	1
r min.	0,6 mm
ALPHA_	0
UNSPSC	31171504
Weight	0,281 Kg
ra max.	0,6 mm
Da max.	91 mm
GRS rpm	7100
Oil rpm	8500
da min.	64 mm
hidYobi	16012
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Enclosure	Open
Inventory	2.0
Snap Ring	No
Size (mm)	60x95x11
Prod_Type3	DGBB_SR_OT
Width (mm)	11
Weight / LBS	0.595
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Bearing number	16012
Keyword String	Ball
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Outside Diameter	3.74 Inch 95 Millimeter
Outer Race Width	0.433 Inch 11 Millimeter
Long Description	60MM Bore; 95MM

	Outside Diameter; 11MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Manufacturer Name	NSK
Weight / Kilogram	0.27
Internal Clearance	C0-Medium
Bore Diameter (mm)	60
Outer Diameter (mm)	95
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	8 500 r/min
Internal Special Features	No
(Grease) Lubrication Speed	7 100 r/min
Basic static load rating (C0)	17,5 kN
Basic dynamic load rating (C)	20 kN
Maximum Capacity / Filling Slot	No