



Bearing No. 61806-2RS1

D	42 mm
d	30 mm
B	16 mm
Bore	1.181 Inch 30 Millimeter
Noun	Bearing
UNSPSC	31171504
series:	61
Category	Single Row Ball Bearing
Size (mm)	42x30x16
Snap Ring	No
Enclosure	2 Seals
Inventory	0.0
Width (mm)	16
bore type:	Round
maximum rpm:	9500 RPM
Weight / LBS	0.06
Mass bearing	0.025 kg
D ₂	39.4 mm
Cage Material	Steel
closure type:	Double Sealed
d ₂	32.6 mm
Product Group	B00308
Inch - Metric	Metric
fillet radius:	0.3 mm
cage material:	Steel
overall width:	7 mm
bore diameter:	30 mm
Limiting speed	9500 r/min
Keyword String	Ball

Enclosure Type	Contact Seal
Bearing number	61806-2RS1
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Precision Class	ABEC 1 ISO P0
Manufacturer URL	http://www.skf.com
Long Description	30MM Bore; 42MM Outside Diameter; 7MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	1.654 Inch 42 Millimeter
Outer Race Width	0.276 Inch 7 Millimeter
precision rating:	Not Rated
outside diameter:	42 mm
Weight / Kilogram	0.027
outer ring width:	7 mm
Manufacturer Name	SKF
D _a max.	40 mm
r _a max.	0.3 mm
d _a max.	32.5 mm
Internal Clearance	C0-Medium
d _a min.	32 mm
Bore Diameter (mm)	42
internal clearance:	C0
Outer Diameter (mm)	30
D _a - max.	40 mm
r _{1,2} min.	0.6 mm
Minimum Buy Quantity	N/A
r _a - max.	0.3 mm
d _a - min.	32 mm

d _a - max.	32.5 mm
row type & fill slot:	Single Row Non-Fill Slot
D ₂ ?	39.4 mm
static load capacity:	2.9 kN
r _{1,2} - min.	0.6 mm
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	4.49 kN
Manufacturer Item Number	61806-2RS1
Internal Special Features	No
Basic dynamic load rating C	4.1 kN
operating temperature range:	-40 to +210 °F
Basic dynamic load rating - C	4.5 kN
Maximum Capacity / Filling Slot	No
Fatigue load limit P _u	0.146 kN
Calculation factor k _r	0.015
Calculation factor f ₀	13.9
Calculation factor - k _r	0.015
Calculation factor - f ₀	13.9
Fatigue load limit - P _u	0.146 kN
Basic static load rating C ₀	2.9 kN
Basic static load rating - C ₀	2.9 kN