



Bearing No. NU2330R

|            |             |
|------------|-------------|
| C          | 108 mm      |
| d          | 150 mm      |
| D          | 320 mm      |
| B          | 108 mm      |
| B2         | -           |
| Cu         | 187         |
| Ew         | -           |
| d1         | -           |
| B1         | -           |
| Cr         | 1450        |
| Fw         | 193 mm      |
| C0r        | 1600        |
| r min.     | 4 mm        |
| Weight     | 44.7 Kg     |
| r(min)     | 4           |
| da(min)    | -           |
| db(min)    | 166         |
| db(max)    | 190         |
| dc(min)    | -           |
| r1(min)    | 4           |
| dd(min)    | -           |
| Da(max)    | 304         |
| Db(max)    | -           |
| Db(min)    | -           |
| r1 min.    | 4 mm        |
| ra(max)    | 3           |
| rb(max)    | 3           |
| Oil lub.   | 2300        |
| Size (mm)  | 150x320x108 |
| Width (mm) | 108         |

|                               |            |
|-------------------------------|------------|
| Grease lub.                   | 1500       |
| Bearing No.                   | NU2330R    |
| Bearing number                | NU2330R    |
| (Refer.)Mass(kg)              | 44.7       |
| Bore Diameter (mm)            | 150        |
| Outer Diameter (mm)           | 320        |
| (Grease) Lubrication Speed    | 1500 r/min |
| Basic static load rating (C0) | 1600 kN    |
| Basic dynamic load rating (C) | 1180 kN    |