



**Bearing No. NU2324**

|                   |            |
|-------------------|------------|
| F                 | 154 mm     |
| d                 | 120 mm     |
| D                 | 260 mm     |
| B                 | 86 mm      |
| C                 | 86 mm      |
| E                 | 226 mm     |
| Fw                | 154 mm     |
| Weight            | 21,5 Kg    |
| ra max            | 2.5 mm     |
| db min            | 156 mm     |
| rs min            | 3 mm       |
| Da max            | 247 mm     |
| da max            | 151 mm     |
| da min            | 133 mm     |
| r min.            | 3 mm       |
| r1a max           | 2.5 mm     |
| r1s min           | 3 mm       |
| r1 min.           | 3 mm       |
| Category          | Bearings   |
| Size (mm)         | 120x260x86 |
| Inventory         | 0.0        |
| Nlim (oil)        | 2,800 rpm  |
| Width (mm)        | 86         |
| Product Group     | B04144     |
| Nlim (grease)     | 2,400 rpm  |
| Bearing number    | NU2324     |
| Static load, C0   | 920 kN     |
| Dynamic load, C   | 710 kN     |
| Manufacturer Name | NTN        |
| Weight / Kilogram | 22.2       |

|                                 |             |
|---------------------------------|-------------|
| Bore Diameter (mm)              | 120         |
| Outer Diameter (mm)             | 260         |
| Minimum Buy Quantity            | N/A         |
| Fatigue limit load, Cu          | 92.5 kN     |
| Mass (without HJ ring)          | 21.5 kg     |
| Radial clearance class          | CN          |
| (Grease) Lubrication Speed      | 2 400 r/min |
| Basic static load rating (C0)   | 920 kN      |
| Basic dynamic load rating (C)   | 710 kN      |
| Min operating temperature, Tmin | -40 °C      |
| Max operating temperature, Tmax | 120 °C      |