



Bearing No. NU2324

| | |
|------------|------------|
| C | 86 mm |
| d | 120 mm |
| D | 260 mm |
| B | 86 mm |
| B2 | - |
| Cu | 116 |
| Ew | - |
| d1 | - |
| B1 | - |
| Cr | 886 |
| Fw | 154 mm |
| C0r | 918 |
| r min. | 3 mm |
| Weight | 23.1 Kg |
| r(min) | 3 |
| da(min) | - |
| db(min) | 133 |
| db(max) | 151 |
| dc(min) | - |
| r1(min) | 3 |
| dd(min) | - |
| Da(max) | 247 |
| Db(max) | - |
| Db(min) | - |
| r1 min. | 3 mm |
| ra(max) | 2.5 |
| rb(max) | 2.5 |
| Oil lub. | 3000 |
| Size (mm) | 120x260x86 |
| Width (mm) | 86 |

| | |
|-------------------------------|------------|
| Grease lub. | 2000 |
| Bearing No. | NU2324 |
| Bearing number | NU2324 |
| (Refer.)Mass(kg) | 23.1 |
| Bore Diameter (mm) | 120 |
| Outer Diameter (mm) | 260 |
| (Grease) Lubrication Speed | 2000 r/min |
| Basic static load rating (C0) | 918 kN |
| Basic dynamic load rating (C) | 708 kN |