



Bearing No. NU2313-E-TVP2

|                |  |
|----------------|--|
| E              | 124,5 mm   |
| F              | 82,5 mm  |
| d              | 65 mm  |
| D              | 140 mm   |
| B              | 48 mm  |
| m              | 3,32 kg / Weight   |
| s              | 4 mm / Axial displacement facility from central position |
| Size (mm)      | 65x140x48  |
| Width (mm)     | 48   |
| $n_B$          | 4050 1/min   |
| $n_G$          | 5900 1/min / Limiting speed                              |
| $D_1$          | 118,6 mm   |
| $C_r$          | 295000 N / Dynamic load rating (radial)                  |
| $C_{Or}$       | 285000 N / Static load rating (radial)                   |
| Bearing number | NU2313-E-TVP2  |
| $C_{ur}$       | 54000 N / Fatigue limit load, radial                     |
| $r_{min}$      | 2,1 mm   |
| $r_{1 min}$    | 2,1 mm   |
| $r_{a max}$    | 2,1 mm   |
| $d_{b min}$    | 85 mm  |
| $d_{a min}$    | 77 mm  |
| $d_{a max}$    | 81 mm  |
| $D_{a max}$    | 128 mm   |
| $r_{a1 max}$   | 2,1 mm   |

|                     |     |
|---------------------|-----|
| Bore Diameter (mm)  | 65  |
| Outer Diameter (mm) | 140 |