



Bearing No. SL185006

E	49,6 mm
d	30 mm
D	55 mm
B	34 mm
C	17 mm
s	1,5 mm / Axial displacement
m	0,35 kg / Weight
Bore	1.181 Inch 30 Millimeter
Noun	Bearing
Width	1.339 Inch 34 Millimeter
UNSPSC	31171547
Profile	Complete with Outer and Inner Ring
Category	Cylindrical Roller Bearing
Retainer	No
Inventory	0.0
Separable	No
Size (mm)	30x55x34
Snap Ring	No
Width (mm)	34
Weight / LBS	0.924
Bore Profile	Straight
Cage Material	None
Product Group	B04144
Inch - Metric	Metric
n_G	8100 1/min / Limiting speed
d_1	40 mm

D ₁	45,3 mm
C _r	78000 N / Dynamic load rating (radial)
Relubricatable	Yes
Other Features	Full Complement 3 Rib Inner Ring 1 Rib Outer Ring with Retaining Ring Operating Temperature From -30 to 120 Deg
Bearing number	SL185006
C _{ur}	15000 N / Fatigue limit load, radial
C _{Or}	84000 N / Static load rating (radial)
r _{min}	1 mm
Rolling Element	Cylindrical Roller Bearing
Precision Class	RBEC 1 ISO P0
Long Description	30MM Bore; Straight Bore Profile; 55MM Outside Diameter; 34MM Width; RBEC 1 ISO P0; Double Row; Not Separable; No Snap Ring; Relubricatable; C0-Medium Internal Clearance; No Retainer
Manufacturer URL	http://www.ina.com
Outside Diameter	2.165 Inch 55 Millimeter
Weight / Kilogram	0.419
Manufacturer Name	SCHAEFFLER GROUP
Internal Clearance	C0-Medium
Bore Diameter (mm)	30
Outer Diameter (mm)	55
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.50.00.00

Manufacturer Item Number	SL185006
Number of Rows of Rollers	Double Row