



Bearing No. NKXR25T2Z+IR20×25×20

|                                |                      |
|--------------------------------|----------------------|
| B                              | 20 mm                |
| a                              | 37,7 mm              |
| d                              | 20 mm                |
| F                              | 25 mm                |
| D                              | 37 mm                |
| C                              | 30 mm                |
| C1                             | 11 mm                |
| d1                             | 25 mm                |
| D1                             | 42 mm                |
| D2                             | 43 mm                |
| C2                             | 9,5 mm               |
| r min.                         | 0,6 mm               |
| Weight                         | 0,162 Kg             |
| db min                         | 22 mm                |
| ra max.                        | 0,6 mm               |
| r1 min.                        | 0,3 mm               |
| da min.                        | 39 mm                |
| ra1 max.                       | 0,3 mm               |
| Bearing number                 | NKXR25T2Z+IR20×25×20 |
| Bore Diameter (mm)             | 20                   |
| Outer Diameter (mm)            | 43                   |
| (Grease) Lubrication Speed     | 1800 r/min           |
| Dynamic load rating axial (C)  | 27,3 kN              |
| Static load rating axial (C0)  | 68 kN                |
| Dynamic load rating radial (C) | 14,2 kN              |
| Static load rating radial (C0) | 24 kN                |

