



### Bearing No. 32356

D	580 mm
d	280 mm
T	187 mm
B	175 mm
C	145 mm
a	139,6 mm
e	0.37
Cr	335000
Y0	0.89
db	353
da	319
Y1	1.6
B_	175
Sb	42
C0	5400
Sa	14
D_	580
Z_	18
C_	145
C0r	550000
DA_	69.819
Iso	-
DE_	496.205
D_b	532
DI_	362.436
SBRG	23
SDM_	429.321
D_a2	475
KBRG	3116
yobi	32356

D_a1	552
mass	224
TC-RA	1106
r min.	6 mm
Weight	224 Kg
TC-DA1	73.98
TC-DA2	65.658
TC-SLR	125
Da min	475 mm
LangID	1
ALPHA_	13.833
Db min.	532 mm
Oil rpm	800
db max.	353 mm
Da max.	552 mm
ra max.	5 mm
hidYobi	32356
da min.	319 mm
T-ALP21	27
rb max.	5 mm
T-ALP22	40
T-ALP23	0
GRS rpm	560
inner r	6
outer r	6
r1 min.	6 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	3
inner ra	5
outer rb	5
TC-BET22	50

Size (mm)	280x580x187
Width (mm)	187
Prod_Type3	TRBSR_MD_A
Bearing number	32356
Bore Diameter (mm)	280
Outer Diameter (mm)	580
Calculation factor (e)	0,37
Calculation factor (Y0)	0,89
(Oil) Lubrication Speed	800 r/min
(Grease) Lubrication Speed	560 r/min
Basic dynamic load rating (C)	3300 kN
Basic static load rating (C0)	5400 kN