



Bearing No. NKX40

| | |
|---------------|-----------------|
| d | 40 mm |
| D | 52 mm |
| C | 32 mm |
| Cr | 25.9 kN |
| Ca | 26.9 kN |
| Dw | 2.5 mm |
| Lw | 15.3 mm |
| C2 | 10 mm |
| dw | 40 mm |
| C1 | 13 mm |
| D1 | 60 mm |
| Fw | 40 mm |
| Dw1 | 7.14 mm |
| C0a | 63 kN |
| C0r | 52.5 kN |
| Mass | 0.22 kg |
| rs min | 0.6 mm |
| r min. | 0,6 mm |
| Weight | 0,216 Kg |
| da min | 52 mm |
| ras max | 0.6 mm |
| series: | NKX |
| ra max. | 0,6 mm |
| da min. | 52 mm |
| flanges: | No Flange |
| Category | Roller Bearings |
| Inventory | 0.0 |
| Nlim (oil) | 5,000 rpm |
| maximum rpm: | 5000 RPM |
| Product Group | B04144 |

| | |
|---------------------------------|-------------------------------------|
| closure type: | Open |
| Nlim (grease) | 3,500 rpm |
| bore diameter: | 40 mm |
| overall width: | 32 mm |
| Bearing number | NKX40 |
| Precision class | P0 |
| precision rating: | Not Rated |
| Weight / Kilogram | 0.222 |
| outside diameter: | 61 mm |
| Manufacturer Name | NTN |
| Bore Diameter (mm) | 40 |
| Outer Diameter (mm) | 60 |
| Minimum Buy Quantity | N/A |
| needle bearing type: | Machined Bearing with No Inner Ring |
| static load capacity: | 5350 kgf |
| lubrication hole type: | No Hole |
| dynamic load capacity: | 2650 kgf |
| (Grease) Lubrication Speed | 3500 r/min |
| Static load rating axial (C0) | 63 kN |
| Dynamic load rating axial (C) | 26,9 kN |
| Lubrication hole on outer ring | Oui/Yes |
| Static load rating radial (C0) | 52,5 kN |
| Dynamic load rating radial (C) | 25,9 kN |
| Min operating temperature, Tmin | -20 °C |
| Max operating temperature, Tmax | 120 °C |