



Bearing No. 32930

D	210 mm
d	150 mm
T	38 mm
B	36 mm
C	31 mm
a	36,7 mm
e	0.33
D_	210
Y0	1
Cr	25200
db	162
da	165
Y1	1.8
B_	36
C0	440
Sa	7
Sb	7
C_	31
Z_	31
Iso	-
D_b	201
DE_	193.319
DI_	164.737
DA_	14.585
C0r	45000
SBRG	29
Noun	Bearing
D_a2	195
D_a1	200
yobi	32930

KBRG	3111
mass	3.8
SDM_	179.028
Bore	5.906 Inch 150 Millimeter
TC-RA	468.812
Da min	195 mm
TC-SLR	26
TC-DA2	14.17
TC-DA1	15
r min.	2,5 mm
UNSPSC	31171516
ALPHA_	12.25
LangID	1
Weight	3,8 Kg
inner r	2.5
rb max.	2 mm
T-ALP22	30
GRS rpm	1500
hidYobi	32930
T-ALP23	0
outer r	2
Oil rpm	2000
T-ALP21	24
ra max.	2 mm
Db min.	201 mm
db max.	162 mm
Da max.	200 mm
da min.	165 mm
r1 min.	2 mm
hidTable	ecat_NSTPRM
TC-BET22	50
TC-BET21	1

TC-BET23	0
inner ra	2
outer rb	2
Category	Tapered Roller Bearings Assembly
Component	Assembly
Inventory	0.0
Size (mm)	150x210x38
Prod_Type3	TRBSR_MD_A
Width (mm)	38
Basic Number	32930
Weight / LBS	8.378
Product Group	B04334
Inch - Metric	Metric
Other Features	Standard Angle Pressed Steel Cage
Keyword String	Tapered
Assembly Width	1.496 Inch 38 Millimeter
Bearing number	32930
Precision Class	Standard
Outside Diameter	8.268 Inch 210 Millimeter
Manufacturer URL	http://www.nskamericas.com
Long Description	Assembly; Standard Precision; 150MM Bore; 210MM Outside Diameter; 38MM Assembly Width; Single Row of Rollers
Weight / Kilogram	3.8
Manufacturer Name	NSK
Bore Diameter (mm)	150
Outer Diameter (mm)	210

Minimum Buy Quantity	N/A
Calculation factor (e)	0,33
Number of Tapered Rows	Single Row
Harmonized Tariff Code	8482.20.00.00
Flange Outside Diameter	0 Inch 0 Millimeter
Calculation factor (Y0)	1
(Oil) Lubrication Speed	2000 r/min
Manufacturer Item Number	32930
(Grease) Lubrication Speed	1500 r/min
Basic static load rating (C0)	440 kN
Basic dynamic load rating (C)	247 kN