



Bearing No. NATR 12 PPXA

d	12 mm
D	32 mm
C	14 mm
B	15 mm
Noun	Bearing
Bore	0.472 Inch 12 Millimeter
UNSPSC	31171530
Profile	Yoke Type
Category	Cam Followers Yoke Type
Enclosure	Sealed
Inventory	0.0
Size (mm)	12x32x14
Width (mm)	14
Roller Width	0.551 Inch 14 Millimeter
Weight / LBS	0.157
Product Group	B04144
d ₁	25 mm
Inch - Metric	Metric
d ₁	25 mm
Keyword String	Cam Follower
Other Features	Caged With Flanged Inner Ring 3 Stage Sealing
Relubricatable	Yes
Bearing number	NATR 12 PPXA
Limiting speed	4500 r/min
Rolling Element	Needle Bearing
Roller Diameter	1.26 Inch 32 Millimeter

Long Description	12MM Bore; 32MM Roller Diameter; 14MM Roller Width; Flat Roller; Yoke Type; Sealed; Needle Bearing; Relubricatable
Manufacturer URL	http://www.skf.com
Weight / Kilogram	0.07
Manufacturer Name	SKF
Bore Diameter (mm)	12
Mass support roller	0.066 kg
Outer Diameter (mm)	32
Minimum Buy Quantity	N/A
$r_{1,2}$ min.	0.6 mm
$r_{1,2}$ - min.	0.6 mm
Roller Surface Profile	Flat
Harmonized Tariff Code	8482.40.00.00
Manufacturer Item Number	NATR 12 PPXA
Basic dynamic load rating C	6.6 kN
Basic dynamic load rating - C	6.6 kN
Fatigue load limit P_u	0.95 kN
Fatigue load limit - P_u	0.95 kN
Basic static load rating C_0	8.5 kN
Basic static load rating - C_0	8.5 kN
Maximum static radial loads - F_r	7.6 kN
Maximum static radial loads - F_{0r}	10.8 kN
Maximum dynamic radial loads F_r max.	7.65 kN

Maximum static radial loads F_{0r} max.	10.8 kN
-------------------------------------------	---------