



Bearing No. NATR 15 PPXA

d	15 mm
D	35 mm
C	18 mm
B	19 mm
Noun	Bearing
Bore	0.591 Inch 15 Millimeter
UNSPSC	31171530
Profile	Yoke Type
Category	Cam Followers Yoke Type
Enclosure	Sealed
Inventory	0.0
Size (mm)	15x35x18
Width (mm)	18
Roller Width	0.709 Inch 18 Millimeter
Weight / LBS	0.22
Product Group	B04144
d ₁	27.6 mm
Inch - Metric	Metric
d ₁	27.6 mm
Keyword String	Cam Follower
Other Features	Caged With Flanged Inner Ring 3 Stage Sealing
Relubricatable	Yes
Bearing number	NATR 15 PPXA
Limiting speed	4000 r/min
Rolling Element	Needle Bearing
Roller Diameter	1.378 Inch 35 Millimeter

Long Description	15MM Bore; 35MM Roller Diameter; 18MM Roller Width; Flat Roller; Yoke Type; Sealed; Needle Bearing; Relubricatable
Manufacturer URL	http://www.skf.com
Weight / Kilogram	0.104
Manufacturer Name	SKF
Bore Diameter (mm)	15
Mass support roller	0.095 kg
Outer Diameter (mm)	35
Minimum Buy Quantity	N/A
$r_{1,2}$ min.	0.6 mm
$r_{1,2}$ - min.	0.6 mm
Roller Surface Profile	Flat
Harmonized Tariff Code	8482.40.00.00
Manufacturer Item Number	NATR 15 PPXA
Basic dynamic load rating C	9.52 kN
Basic dynamic load rating - C	9.5 kN
Fatigue load limit P_u	1.56 kN
Fatigue load limit - P_u	1.6 kN
Basic static load rating C_0	13.7 kN
Basic static load rating - C_0	13.7 kN
Maximum static radial loads - F_r	11.4 kN
Maximum static radial loads - F_{0r}	16.3 kN
Maximum dynamic radial loads F_r max.	11.4 kN

Maximum static radial loads F_{0r} max.	16.3 kN
---	---------