



**Bearing No. NATR 17 X**

d	17 mm
D	40 mm
C	20 mm
B	21 mm
Noun	Bearing
Bore	0.669 Inch   17 Millimeter
UNSPSC	31171530
Profile	Yoke Type
Category	Cam Followers Yoke Type
Enclosure	Sealed
Inventory	0.0
Size (mm)	17x40x20
Width (mm)	20
Roller Width	0.787 Inch   20 Millimeter
Weight / LBS	0.309
Product Group	B04144
Inch - Metric	Metric
d <sub>1</sub>	31.5 mm
d <sub>1</sub>	31.5 mm
Keyword String	Cam Follower
Other Features	Caged   With Flanged Inner Ring   Gap Seal
Relubricatable	Yes
Bearing number	NATR 17 X
Limiting speed	3400 r/min
Rolling Element	Needle Bearing
Roller Diameter	1.575 Inch   40 Millimeter

Long Description	17MM Bore; 40MM Roller Diameter; 20MM Roller Width; Flat Roller; Yoke Type; Sealed; Needle Bearing; Relubricatable
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Weight / Kilogram	0.14
Manufacturer Name	SKF
Bore Diameter (mm)	17
Mass support roller	0.14 kg
Outer Diameter (mm)	40
Minimum Buy Quantity	N/A
$r_{1,2}$ min.	1 mm
$r_{1,2}$ - min.	1 mm
Roller Surface Profile	Flat
Harmonized Tariff Code	8482.40.00.00
Manufacturer Item Number	NATR 17 X
Basic dynamic load rating C	10.5 kN
Basic dynamic load rating - C	10.5 kN
Fatigue load limit $P_u$	1.73 kN
Fatigue load limit - $P_u$	1.7 kN
Basic static load rating $C_0$	14.6 kN
Basic static load rating - $C_0$	14.6 kN
Maximum static radial loads - $F_r$	12.5 kN
Maximum static radial loads - $F_{0r}$	18 kN
Maximum dynamic radial loads $F_r$ max.	12.5 kN

Maximum static radial loads $F_{0r}$ max.	18 kN
---	-------