



Bearing No. NATR 25 PPXA

d	25 mm
D	52 mm
C	24 mm
B	25 mm
Noun	Bearing
Bore	0.984 Inch 25 Millimeter
UNSPSC	31171530
Profile	Yoke Type
Category	Cam Followers Yoke Type
Enclosure	Sealed
Inventory	0.0
Size (mm)	25x52x24
Width (mm)	24
Roller Width	0.945 Inch 24 Millimeter
Weight / LBS	0.617
Product Group	B04144
Inch - Metric	Metric
d ₁	41.5 mm
d ₁	41.5 mm
Keyword String	Cam Follower
Other Features	Caged With Flanged Inner Ring 3 Stage Sealing
Relubricatable	Yes
Bearing number	NATR 25 PPXA
Limiting speed	2400 r/min
Rolling Element	Needle Bearing
Roller Diameter	2.047 Inch 52 Millimeter

Long Description	25MM Bore; 52MM Roller Diameter; 24MM Roller Width; Flat Roller; Yoke Type; Sealed; Needle Bearing; Relubricatable
Manufacturer URL	http://www.skf.com
Weight / Kilogram	0.28
Manufacturer Name	SKF
Bore Diameter (mm)	25
Mass support roller	0.27 kg
Outer Diameter (mm)	52
Minimum Buy Quantity	N/A
$r_{1,2}$ min.	1 mm
$r_{1,2}$ - min.	1 mm
Roller Surface Profile	Flat
Harmonized Tariff Code	8482.40.00.00
Manufacturer Item Number	NATR 25 PPXA
Basic dynamic load rating C	14.7 kN
Basic dynamic load rating - C	14.7 kN
Fatigue load limit P_u	3.1 kN
Fatigue load limit - P_u	3.1 kN
Basic static load rating C_0	25.5 kN
Basic static load rating - C_0	25.5 kN
Maximum static radial loads - F_r	21.6 kN
Maximum static radial loads - F_{0r}	31 kN
Maximum dynamic radial loads F_r max.	21.6 kN

Maximum static radial loads F_{0r} max.	31 kN
-------------------------------------------	-------