



**Bearing No. NATR 6 PPA**

B	12 mm
D	19 mm
d	6 mm
C	11 mm
Bore	0.236 Inch   6 Millimeter
Noun	Bearing
UNSPSC	31171530
Profile	Yoke Type
Category	Cam Followers Yoke Type
Size (mm)	6x19x11
Enclosure	Sealed
Inventory	0.0
Width (mm)	11
Weight / LBS	0.044
Roller Width	0.433 Inch   11 Millimeter
maximum rpm:	5600 RPM
Product Group	B04120
roller width:	12 mm
roller shape:	Crowned
Inch - Metric	Metric
closure type:	Sealed
d <sub>1</sub>	15 mm
d <sub>1</sub>	15 mm
Keyword String	Cam Follower
Other Features	Caged   With Flanged Inner Ring   3 Stage Sealing
Bearing number	NATR 6 PPA
bore diameter:	6 mm

Relubricatable	Yes
Limiting speed	5600 r/min
standards met:	ANSI/ABMA Standard 18.1
Rolling Element	Needle Bearing
finish/coating:	Uncoated
Roller Diameter	0.748 Inch   19 Millimeter
roller material:	Chrome Steel
Long Description	6MM Bore; 19MM Roller Diameter; 11MM Roller Width; Crowned Roller; Yoke Type; Sealed; Needle Bearing; Relubricatable
roller diameter:	19 mm
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
bearing element:	Needle Rollers
Weight / Kilogram	0.023
Manufacturer Name	SKF
Bore Diameter (mm)	6
Mass support roller	0.019 kg
Outer Diameter (mm)	19
Minimum Buy Quantity	N/A
r <sub>1,2</sub> min.	0.15 mm
Harmonized Tariff Code	8482.40.00.00
Roller Surface Profile	Crowned
r <sub>1,2</sub> - min.	0.15 mm
Manufacturer Item Number	NATR 6 PPA
lubrication hole location:	Inner Ring
axial static load capacity:	3.8 kN
Basic dynamic load rating C	3.47 kN

radial static load capacity:	5.5 kN
axial dynamic load capacity:	3.47 kN
operating temperature range:	Maximum of +280 °F
Basic dynamic load rating - C	3.5 kN
radial dynamic load capacity:	3.8 kN
Fatigue load limit $P_u$	0.415 kN
Fatigue load limit - $P_u$	0.415 kN
Basic static load rating $C_0$	3.8 kN
Basic static load rating - $C_0$	3.8 kN
Maximum static radial loads - $F_r$	3.8 kN
Maximum static radial loads - $F_{0r}$	5.5 kN
Maximum dynamic radial loads $F_r$ max.	3.8 kN
Maximum static radial loads $F_{0r}$ max.	5.5 kN