



Bearing No. NATR 6 X

d	6 mm
D	19 mm
C	11 mm
B	12 mm
Noun	Bearing
Bore	0.236 Inch 6 Millimeter
UNSPSC	31171530
Profile	Yoke Type
Category	Cam Followers Yoke Type
Enclosure	Sealed
Inventory	0.0
Size (mm)	6x19x11
Width (mm)	11
Roller Width	0.433 Inch 11 Millimeter
Weight / LBS	0.044
Product Group	B04144
Inch - Metric	Metric
d ₁	15 mm
d ₁	15 mm
Keyword String	Cam Follower
Other Features	Caged With Flanged Inner Ring Gap Seal
Relubricatable	Yes
Bearing number	NATR 6 X
Limiting speed	5600 r/min
Rolling Element	Needle Bearing
Roller Diameter	0.748 Inch 19 Millimeter
Long Description	6MM Bore; 19MM Roller

	Diameter; 11MM Roller Width; Flat Roller; Yoke Type; Sealed; Needle Bearing; Relubricatable
Manufacturer URL	http://www.skf.com
Weight / Kilogram	0.023
Manufacturer Name	SKF
Bore Diameter (mm)	6
Mass support roller	0.02 kg
Outer Diameter (mm)	19
Minimum Buy Quantity	N/A
r _{1,2} min.	0.15 mm
r _{1,2} - min.	0.15 mm
Roller Surface Profile	Flat
Harmonized Tariff Code	8482.40.00.00
Manufacturer Item Number	NATR 6 X
Basic dynamic load rating C	3.47 kN
Basic dynamic load rating - C	3.5 kN
Fatigue load limit P _u	0.415 kN
Fatigue load limit - P _u	0.415 kN
Basic static load rating C ₀	3.8 kN
Basic static load rating - C ₀	3.8 kN
Maximum static radial loads - F _r	3.8 kN
Maximum static radial loads - F _{0r}	5.5 kN
Maximum dynamic radial loads F _r max.	3.8 kN
Maximum static radial loads F _{0r} max.	5.5 kN

