



Bearing No. B7026-C-T-P4S

|                     |   |
|---------------------|---|
| D                   | 200 mm  |
| d                   | 130 mm  |
| B                   | 33 mm   |
| a                   | 39 mm   |
| m                   | 3,16 kg / Weight  |
| ?                   | 15 ° / Angle  |
| Size (mm)           | 130x200x33  |
| Width (mm)          | 33  |
| d <sub>a</sub>      | 142 mm / Tolerance:<br>h12  |
| C <sub>r</sub>      | 149000 N / Dynamic<br>load rating (radial)                              |
| D <sub>a</sub>      | 189 mm / Tolerance:<br>H12  |
| C <sub>0r</sub>     | 107000 N / Static load<br>rating (radial)                               |
| Bearing number      | B7026-C-T-P4S   |
| r <sub>min</sub>    | 2 mm  |
| n <sub>G OI</sub>   | 10000 1/min / Limiting<br>speed for minimal<br>quantity oil lubrication |
| r <sub>a max</sub>  | 2 mm  |
| r <sub>1 min</sub>  | 2 mm  |
| r <sub>a1 max</sub> | 1 mm  |
| Bore Diameter (mm)  | 130   |
| n <sub>G Fett</sub> | 6700 1/min / Limiting<br>speed for grease<br>lubrication                |
| Outer Diameter (mm) | 200   |