



Bearing No. 32940

D	280 mm
d	200 mm
T	51 mm
B	48 mm
C	41 mm
a	53,4 mm
e	0.37
Cr	42000
Y0	0.88
db	217
da	218
Y1	1.6
B_	48
Sb	10
C0	780
Sa	9
D_	280
Z_	32
C_	41
C0r	80000
DA_	18.655
Iso	-
DE_	258.223
D_b	269
DI_	222.096
SBRG	29
SDM_	240.16
D_a2	256
KBRG	3111
yobi	32940

D_a1	268
mass	9.26
TC-RA	551.897
r min.	3 mm
Weight	9,26 Kg
TC-DA1	19.264
TC-DA2	18.045
TC-SLR	35
Da min	256 mm
LangID	1
ALPHA_	14
Db min.	269 mm
Oil rpm	1500
db max.	217 mm
Da max.	268 mm
ra max.	2,5 mm
hidYobi	32940
da min.	218 mm
T-ALP21	28
rb max.	2 mm
T-ALP22	0
T-ALP23	0
GRS rpm	1100
inner r	3
outer r	2.5
r1 min.	2,5 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	2
inner ra	2.5
outer rb	2
TC-BET22	0

Size (mm)	200x280x51
Width (mm)	51
Prod_Type3	TRBSR_MD_A
Bearing number	32940
Bore Diameter (mm)	200
Outer Diameter (mm)	280
Calculation factor (e)	0,37
Calculation factor (Y0)	0,88
(Oil) Lubrication Speed	1500 r/min
(Grease) Lubrication Speed	1100 r/min
Basic dynamic load rating (C)	410 kN
Basic static load rating (C0)	780 kN