



Bearing No. 32960

D	420 mm
d	300 mm
T	76 mm
B	72 mm
C	62 mm
a	79,3 mm
e	0.37
Cr	91000
Y0	0.88
db	326
da	321
Y1	1.6
B_	72
Sb	14
C0	1820
Sa	13
D_	420
Z_	33
C_	62
C0r	186000
DA_	28.089
Iso	-
DE_	389.459
D_b	405
DI_	334.571
SBRG	29
SDM_	362.015
D_a2	386
KBRG	3111
yobi	32960

D_a1	406
mass	30.5
TC-RA	830.668
r min.	4 mm
Weight	30,5 Kg
TC-DA1	28.994
TC-DA2	27.183
TC-SLR	52
Da min	386 mm
LangID	1
ALPHA_	14
Db min.	405 mm
Oil rpm	950
db max.	326 mm
Da max.	406 mm
ra max.	3 mm
hidYobi	32960
da min.	321 mm
T-ALP21	28
rb max.	2,5 mm
T-ALP22	0
T-ALP23	0
GRS rpm	710
inner r	4
outer r	3
r1 min.	3 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	2
inner ra	3
outer rb	2.5
TC-BET22	0

Size (mm)	300x420x76
Width (mm)	76
Prod_Type3	TRBSR_MD_A
Bearing number	32960
Bore Diameter (mm)	300
Outer Diameter (mm)	420
Calculation factor (e)	0,37
Calculation factor (Y0)	0,88
(Oil) Lubrication Speed	950 r/min
(Grease) Lubrication Speed	710 r/min
Basic dynamic load rating (C)	895 kN
Basic static load rating (C0)	1820 kN