



### Bearing No. 7076 BM

a	238 mm
d	380 mm
D	560 mm
B	82 mm
Size (mm)	560x380x82
Width (mm)	82
Mass bearing	64.7 kg
d <sub>1</sub>	450.63 mm
d <sub>2</sub>	419.05 mm
D <sub>1</sub>	492.33 mm
Limiting speed	1200 r/min
Bearing number	7076 BM
Reference speed	1100 r/min
d <sub>a</sub> min.	398 mm
D <sub>a</sub> max.	542 mm
D <sub>b</sub> max.	551 mm
Bore Diameter (mm)	560
r <sub>a</sub> max.	4 mm
r <sub>b</sub> max.	2 mm
Outer Diameter (mm)	380
r <sub>3,4</sub> min.	2 mm
r <sub>1,2</sub> min.	5 mm
Calculation factor A	11.9
Calculation factor e	1.14
Calculation factor X	0.57
r <sub>b</sub> - max.	2 mm
r <sub>a</sub> - max.	4 mm
D <sub>b</sub> - max.	551 mm
D <sub>a</sub> - max.	542 mm
d <sub>a</sub> - min.	398 mm

$D_1$ ?	492.33 mm
$d_1$ ?	450.63 mm
$d_2$ ?	419.05 mm
$r_{1,2}$ - min.	5 mm
$r_{3,4}$ - min.	2 mm
Calculation factor - X	0.35
Calculation factor - e	1.14
Basic dynamic load rating C	468 kN
Basic dynamic load rating - C	468 kN
Calculation factor $k_r$	0.083
Calculation factor $Y_0$	0.52
Calculation factor $Y_2$	0.93
Calculation factor $Y_1$	0.55
Fatigue load limit $P_u$	16.6 kN
Calculation factor - $Y_0$	0.26
Calculation factor - $Y_1$	
Calculation factor - $k_a$	0.9
Calculation factor - $k_r$	0.083
Calculation factor - $Y_2$	0.57
Fatigue load limit - $P_u$	16.6 kN
Basic static load rating $C_0$	850 kN
Basic static load rating - $C_0$	850 kN