



Bearing No. BT4B 334128/HA1

D	546.1 mm
d	384.175 mm
B	400.05 mm
T	400.05 mm
Size (mm)	546.1x384.175x400.05
Width (mm)	400,05
Mass bearing	340 kg
Bearing number	BT4B 334128/HA1
Thrust factor K	1.76
Thrust factor - K	1.76
Bore Diameter (mm)	546,1
Outer Diameter (mm)	384,175
Calculation factor e	0.33
$r_{1,2}$ min.	3.3 mm
$r_{3,4}$ min.	3.3 mm
d_1 ?	418 mm
D_1 ?	484 mm
Calculation factor - e	0.33
$r_{3,4}$ - min.	3.3 mm
$r_{1,2}$ - min.	3.3 mm
Design variant/feature	TQOT
Basic dynamic load rating C	6440 kN
Basic dynamic load rating - C	6440 kN
Calculation factor Y_2	3
Fatigue load limit P_u	1290 kN
Calculation factor Y_1	2
Calculation factor Y_0	2
Calculation factor - Y_0	2
Calculation factor - Y	3

	2
Fatigue load limit - P_u	1290 kN
Calculation factor - Y_1	2
Basic static load rating C_0	16600 kN
Basic static load rating - C_0	16600 kN
Comparative radial load rating C_F	1730 kN
Comparative axial load rating C_{Fa}	278 kN
Comparative axial load rating - C_{Fa}	278 kN
Comparative radial load rating - C_F	1730 kN