



Bearing No. BT4B 332596/HA4

| | |
|-------------------------------------|-----------------|
| D | 990.6 mm |
| d | 749.3 mm |
| B | 650 mm |
| T | 577 mm |
| Size (mm) | 990.6x749.3x650 |
| Width (mm) | 650 |
| Mass bearing | 1500 kg |
| Bearing number | BT4B 332596/HA4 |
| Thrust factor K | 1.76 |
| Thrust factor - K | 1.76 |
| Bore Diameter (mm) | 990,6 |
| Outer Diameter (mm) | 749,3 |
| r _{1,2} min. | 6.4 mm |
| Calculation factor e | 0.33 |
| r _{3,4} min. | 3.3 mm |
| d ₁ ? | 858 mm |
| D ₁ ? | 952 mm |
| Calculation factor - e | 0.33 |
| r _{3,4} - min. | 3.3 mm |
| Design variant/feature | TQIT.1 |
| Basic dynamic load rating C | 15100 kN |
| Basic dynamic load rating - C | 15100 kN |
| Calculation factor Y ₂ | 3 |
| Fatigue load limit P _u | 2850 kN |
| Calculation factor Y ₁ | 2 |
| Calculation factor Y ₀ | 2 |
| Calculation factor - Y ₀ | 2 |
| Calculation factor - Y ₁ | 2 |
| | |

| | |
|--|----------|
| Fatigue load limit - P_u | 2850 kN |
| Calculation factor - Y_2 | 3 |
| Basic static load rating C_0 | 45500 kN |
| Basic static load rating - C_0 | 45500 kN |
| Comparative radial load rating C_F | 4050 kN |
| Comparative axial load rating C_{Fa} | 659 kN |
| Comparative axial load rating - C_{Fa} | 659 kN |
| Comparative radial load rating - C_F | 4050 kN |