



Bearing No. BT4B 332602/HA4

D	1219.2 mm
d	889 mm
B	880 mm
T	784.225 mm
Size (mm)	1219.2x889x880
Width (mm)	880
Mass bearing	3340 kg
Bearing number	BT4B 332602/HA4
Thrust factor K	1.76
Thrust factor - K	1.76
Bore Diameter (mm)	1219,2
Outer Diameter (mm)	889
r <sub>1,2</sub> min.	9.7 mm
Calculation factor e	0.33
r <sub>3,4</sub> min.	3.3 mm
d <sub>1</sub> ?	1030 mm
D <sub>1</sub> ?	1165 mm
Calculation factor - e	0.33
r <sub>3,4</sub> - min.	3.3 mm
Design variant/feature	TQIT.1
Basic dynamic load rating C	27000 kN
Basic dynamic load rating - C	27000 kN
Calculation factor Y <sub>2</sub>	3
Fatigue load limit P <sub>u</sub>	4550 kN
Calculation factor Y <sub>1</sub>	2
Calculation factor Y <sub>0</sub>	2
Calculation factor - Y <sub>0</sub>	2
Calculation factor - Y <sub>1</sub>	2

Fatigue load limit - $P_u$	4550 kN
Calculation factor - $Y_2$	3
Basic static load rating $C_0$	78000 kN
Basic static load rating - $C_0$	78000 kN
Comparative radial load rating $C_F$	7200 kN
Comparative axial load rating $C_{Fa}$	1180 kN
Comparative axial load rating - $C_{Fa}$	1180 kN
Comparative radial load rating - $C_F$	7200 kN