



**Bearing No. BT4B 332658/HA4**

D	812.8 mm
d	581.025 mm
B	641.35 mm
T	571.5 mm
Size (mm)	812.8x581.025x641.35
Width (mm)	641,35
Mass bearing	1100 kg
Bearing number	BT4B 332658/HA4
Thrust factor K	1.76
Thrust factor - K	1.76
Bore Diameter (mm)	812,8
Outer Diameter (mm)	581,025
$r_{1,2}$ min.	6.4 mm
Calculation factor e	0.33
$r_{3,4}$ min.	1.5 mm
$d_1$ ?	678 mm
$D_1$ ?	774 mm
Calculation factor - e	0.33
$r_{3,4}$ - min.	6.4 mm
Design variant/feature	TQIT
Basic dynamic load rating C	12100 kN
Basic dynamic load rating - C	12100 kN
Calculation factor $Y_2$	3
Fatigue load limit $P_u$	2160 kN
Calculation factor $Y_1$	2
Calculation factor $Y_0$	2
Calculation factor - $Y_0$	2
Calculation factor - $Y_1$	2

Fatigue load limit - $P_u$	2160 kN
Calculation factor - $Y_2$	3
Basic static load rating $C_0$	32000 kN
Basic static load rating - $C_0$	32000 kN
Comparative radial load rating $C_F$	3250 kN
Comparative axial load rating $C_{Fa}$	528 kN
Comparative axial load rating - $C_{Fa}$	528 kN
Comparative radial load rating - $C_F$	3250 kN