



Bearing No. BT4B 332668/HA1

D	447.675 mm
d	323.452 mm
B	414.338 mm
T	323.85 mm
Size (mm)	447.675x323.452x414.338
Width (mm)	414,338
Mass bearing	200 kg
Bearing number	BT4B 332668/HA1
Thrust factor K	1.74
Thrust factor - K	1.74
Bore Diameter (mm)	447,675
Outer Diameter (mm)	323,452
r <sub>1,2</sub> min.	6 mm
Calculation factor e	0.33
r <sub>3,4</sub> min.	1.5 mm
d <sub>1</sub> ?	389 mm
D <sub>1</sub> ?	420 mm
Calculation factor - e	0.33
r <sub>3,4</sub> - min.	1.5 mm
Design variant/feature	TQIT
Basic dynamic load rating C	4400 kN
Basic dynamic load rating - C	4400 kN
Calculation factor Y <sub>2</sub>	3
Fatigue load limit P <sub>u</sub>	880 kN
Calculation factor Y <sub>1</sub>	2
Calculation factor Y <sub>0</sub>	2
Calculation factor - Y <sub>0</sub>	2
Calculation factor - Y <sub>1</sub>	2

Fatigue load limit - $P_u$	880 kN
Calculation factor - $Y_2$	3
Basic static load rating $C_0$	10800 kN
Basic static load rating - $C_0$	10800 kN
Comparative radial load rating $C_F$	1160 kN
Comparative axial load rating $C_{Fa}$	193 kN
Comparative axial load rating - $C_{Fa}$	193 kN
Comparative radial load rating - $C_F$	1160 kN