



Bearing No. BT4B 332786/HA4

D	1181.1 mm
d	872.769 mm
B	714.375 mm
T	628.65 mm
Size (mm)	1181.1x872.769x714.375
Width (mm)	714,375
Mass bearing	2450 kg
Bearing number	BT4B 332786/HA4
Thrust factor K	1.76
Thrust factor - K	1.76
Bore Diameter (mm)	1181,1
Outer Diameter (mm)	872,769
r <sub>1,2</sub> min.	9.7 mm
Calculation factor e	0.33
r <sub>3,4</sub> min.	1.5 mm
d <sub>1</sub> ?	998 mm
D <sub>1</sub> ?	1130 mm
Calculation factor - e	0.33
r <sub>3,4</sub> - min.	3.3 mm
Design variant/feature	TQIT.1
Basic dynamic load rating C	20900 kN
Basic dynamic load rating - C	20900 kN
Calculation factor Y <sub>2</sub>	3
Fatigue load limit P <sub>u</sub>	3550 kN
Calculation factor Y <sub>1</sub>	2
Calculation factor Y <sub>0</sub>	2
Calculation factor - Y <sub>0</sub>	2
Calculation factor - Y <sub>1</sub>	2

Fatigue load limit - $P_u$	3550 kN
Calculation factor - $Y_2$	3
Basic static load rating $C_0$	57000 kN
Basic static load rating - $C_0$	57000 kN
Comparative radial load rating $C_F$	5600 kN
Comparative axial load rating $C_{Fa}$	909 kN
Comparative axial load rating - $C_{Fa}$	909 kN
Comparative radial load rating - $C_F$	5600 kN