



Bearing No. BT4B 332928/HA1

D	933.45 mm
d	669.925 mm
B	725.488 mm
T	649.288 mm
Size (mm)	933.45x669.925x725.48 8
Width (mm)	725,488
Mass bearing	1700 kg
Bearing number	BT4B 332928/HA1
Thrust factor K	1.76
Thrust factor - K	1.76
Bore Diameter (mm)	933,45
Outer Diameter (mm)	669,925
r _{1,2} min.	6.4 mm
Calculation factor e	0.33
r _{3,4} min.	1.5 mm
d ₁ ?	785 mm
D ₁ ?	890 mm
Calculation factor - e	0.33
r _{3,4} - min.	1.5 mm
Design variant/feature	TQIT
Basic dynamic load rating C	17200 kN
Basic dynamic load rating - C	17200 kN
Calculation factor Y ₂	3
Fatigue load limit P _u	3150 kN
Calculation factor Y ₁	2
Calculation factor Y ₀	2
Calculation factor - Y ₀	2
Calculation factor - Y ₁	2

Fatigue load limit - P_u	3150 kN
Calculation factor - Y_2	3
Basic static load rating C_0	49000 kN
Basic static load rating - C_0	49000 kN
Comparative radial load rating C_F	4650 kN
Comparative axial load rating C_{Fa}	750 kN
Comparative axial load rating - C_{Fa}	750 kN
Comparative radial load rating - C_F	4650 kN