



Bearing No. BT4B 332933/HA1

D	736.6 mm
d	530.225 mm
B	579.438 mm
T	519.112 mm
Size (mm)	736.6x530.225x579.438
Width (mm)	579,438
Mass bearing	865 kg
Bearing number	BT4B 332933/HA1
Thrust factor K	1.76
Thrust factor - K	1.76
Bore Diameter (mm)	736,6
Outer Diameter (mm)	530,225
r <sub>1,2</sub> min.	6.4 mm
Calculation factor e	0.33
r <sub>3,4</sub> min.	1.5 mm
d <sub>1</sub> ?	605 mm
D <sub>1</sub> ?	702 mm
Calculation factor - e	0.33
r <sub>3,4</sub> - min.	6.4 mm
Design variant/feature	TQIT
Basic dynamic load rating C	11200 kN
Basic dynamic load rating - C	11200 kN
Calculation factor Y <sub>2</sub>	3
Fatigue load limit P <sub>u</sub>	2160 kN
Calculation factor Y <sub>1</sub>	2
Calculation factor Y <sub>0</sub>	2
Calculation factor - Y <sub>0</sub>	2
Calculation factor - Y <sub>1</sub>	2

Fatigue load limit - $P_u$	2160 kN
Calculation factor - $Y_2$	3
Basic static load rating $C_0$	31000 kN
Basic static load rating - $C_0$	31000 kN
Comparative radial load rating $C_F$	3000 kN
Comparative axial load rating $C_{Fa}$	491 kN
Comparative axial load rating - $C_{Fa}$	491 kN
Comparative radial load rating - $C_F$	3000 kN