



Bearing No. BT4B 332943/HA4

D	1035.05 mm
d	744.538 mm
B	812.8 mm
T	727.075 mm
Size (mm)	1035.05x744.538x812.8
Width (mm)	812,8
Mass bearing	2350 kg
Bearing number	BT4B 332943/HA4
Thrust factor K	1.76
Thrust factor - K	1.76
Bore Diameter (mm)	1035,05
Outer Diameter (mm)	744,538
r <sub>1,2</sub> min.	9.7 mm
Calculation factor e	0.33
r <sub>3,4</sub> min.	1.5 mm
d <sub>1</sub> ?	858 mm
D <sub>1</sub> ?	987 mm
Calculation factor - e	0.33
r <sub>3,4</sub> - min.	1.5 mm
Design variant/feature	TQIT.1
Basic dynamic load rating C	20500 kN
Basic dynamic load rating - C	20500 kN
Calculation factor Y <sub>2</sub>	3
Fatigue load limit P <sub>u</sub>	3600 kN
Calculation factor Y <sub>1</sub>	2
Calculation factor Y <sub>0</sub>	2
Calculation factor - Y <sub>0</sub>	2
Calculation factor - Y <sub>1</sub>	2

Fatigue load limit - $P_u$	3600 kN
Calculation factor - $Y_2$	3
Basic static load rating $C_0$	58500 kN
Basic static load rating - $C_0$	58500 kN
Comparative radial load rating $C_F$	5500 kN
Comparative axial load rating $C_{Fa}$	909 kN
Comparative axial load rating - $C_{Fa}$	909 kN
Comparative radial load rating - $C_F$	5500 kN