



Bearing No. BT4B 328828 G/HA1

D	438.048 mm
d	304.648 mm
B	280.99 mm
T	279.4 mm
?	15 °
?	15 °
Size (mm)	438.048x304.648x280.99
Width (mm)	280,99
Mass bearing	135 kg
Bearing number	BT4B 328828 G/HA1
Thrust factor K	1.24
Thrust factor - K	1.24
Bore Diameter (mm)	438,048
Outer Diameter (mm)	304,648
r <sub>1,2</sub> min.	2 mm
r <sub>3,4</sub> min.	4.8 mm
Calculation factor e	0.48
D <sub>1</sub> ?	385 mm
d <sub>1</sub> ?	337 mm
Design variant/feature	TQO/GWI
r <sub>1,2</sub> - min.	2 mm
r <sub>3,4</sub> - min.	4.8 mm
Calculation factor - e	0.48
Basic dynamic load rating C	3080 kN
Basic dynamic load rating - C	3080 kN
Fatigue load limit P <sub>u</sub>	585 kN
Calculation factor Y <sub>2</sub>	2.1
Calculation factor Y <sub>1</sub>	1.4

Calculation factor $Y_0$	1.4
Calculation factor - $Y_0$	1.4
Calculation factor - $Y_2$	2.1
Fatigue load limit - $P_u$	585 kN
Calculation factor - $Y_1$	1.4
Basic static load rating $C_0$	6950 kN
Basic static load rating - $C_0$	6950 kN
Comparative radial load rating $C_F$	815 kN
Comparative axial load rating $C_{Fa}$	190 kN
Comparative axial load rating - $C_{Fa}$	190 kN
Comparative radial load rating - $C_F$	815 kN