



Bearing No. 71805 ACD/HCP4

D	37 mm
d	25 mm
B	7 mm
a	10.8 mm
Ball - z	20
Size (mm)	37x25x7
Width (mm)	7
Mass bearing	0.019 kg
d_n	29.5 mm
d_n	29.5 mm
D_1	33.1 mm
d_1	29.1 mm
d_2	29.1 mm
D_1	33.1 mm
d_2	29.1 mm
d_1	29.1 mm
Bearing number	71805 ACD/HCP4
Preload class A	67 N/micron
G_{ref}	0.21 cm ³
Preload class C	142 N/micron
Preload class B	105 N/micron
Number of balls z	20
Bore Diameter (mm)	37
r_b max.	0.15 mm
r_a max.	0.3 mm
D_b max.	36.2 mm
D_a max.	35 mm
d_a min.	27 mm
d_b min.	27 mm

Outer Diameter (mm)	25
D _b - max.	36.2 mm
d _a - min.	27 mm
Calculation factor e	0.68
Calculation factor f	1.11
r _b - max.	0.15 mm
D _a - max.	35 mm
r _a - max.	0.3 mm
r _{3,4} min.	0.15 mm
r _{1,2} min.	0.3 mm
Ball - D _w	3.175 mm
d _b - min.	27 mm
r _{1,2} - min.	0.3 mm
r _{3,4} - min.	0.15 mm
Calculation factor - e	0.68
Calculation factor - f	1.11
Basic dynamic load rating C	3.9 kN
Ball diameter D _w	3.175 mm
Preload class B G _B	105 N
Preload class C G _C	210 N
Basic dynamic load rating - C	3.9 kN
Preload class A G _A	35 N
Preload class B - G _B	105 N
Preload class C - G _C	210 N
Preload class A - G _A	35 N
Fatigue load limit P _u	0.129 kN
Calculation factor f ₁	0.97
Calculation factor f _{2C}	1.17
Calculation factor f _{2A}	1
Calculation factor f _{HC}	1.02

Calculation factor f_{2B}	1.09
Limiting speed for oil lubrication	63000 mm/min
Fatigue load limit - P_u	0.129 kN
Calculation factor - f_1	0.97
Calculation factor - Y_2	1.41
Calculation factor - X_2	0.67
Calculation factor - Y_1	0.92
Calculation factor - Y_0	0.76
Calculation factor - f_{HC}	1.02
Calculation factor - f_{2A}	1
Calculation factor - f_{2C}	1.17
Calculation factor - f_{2B}	1.09
Limiting speed for grease lubrication	40000 r/min
Basic static load rating C_0	3.05 kN
Static axial stiffness, preload class B	105 N/ μ m
Static axial stiffness, preload class A	67 N/ μ m
Attainable speed for grease lubrication	40000 r/min
Static axial stiffness, preload class C	142 N/ μ m
Basic static load rating - C_0	3 kN
Attainable speed for oil-air lubrication	63000 r/min
Reference grease quantity G_{ref}	0.21 cm ³
Calculation factor (single, tandem) Y_2	0.87
Calculation factor	0.38

(single, tandem) Y_0	
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67