



Bearing No. 71805 ACD/P4

D	37 mm
d	25 mm
B	7 mm
a	10.8 mm
Ball - z	20
Size (mm)	37x25x7
Width (mm)	7
Mass bearing	0.021 kg
d _n	29.5 mm
d _n	29.5 mm
D ₁	33.1 mm
d ₁	29.1 mm
d ₂	29.1 mm
D ₁	33.1 mm
d ₂	29.1 mm
d ₁	29.1 mm
Bearing number	71805 ACD/P4
Preload class A	60 N/micron
G _{ref}	0.21 cm ³
Preload class C	128 N/micron
Preload class B	95 N/micron
Number of balls z	20
Bore Diameter (mm)	37
r _b max.	0.15 mm
r _a max.	0.3 mm
D _b max.	36.2 mm
D _a max.	35 mm
d _a min.	27 mm
d _b min.	27 mm

Outer Diameter (mm)	25
D_b - max.	36.2 mm
d_a - min.	27 mm
Calculation factor e	0.68
Calculation factor f	1.11
r_b - max.	0.15 mm
D_a - max.	35 mm
r_a - max.	0.3 mm
$r_{3,4}$ min.	0.15 mm
$r_{1,2}$ min.	0.3 mm
Ball - D_w	3.175 mm
d_b - min.	27 mm
$r_{1,2}$ - min.	0.3 mm
$r_{3,4}$ - min.	0.15 mm
Calculation factor - e	0.68
Calculation factor - f	1.11
Basic dynamic load rating C	3.9 kN
Ball diameter D_w	3.175 mm
Preload class B G_B	105 N
Preload class C G_C	210 N
Basic dynamic load rating - C	3.9 kN
Preload class A G_A	35 N
Preload class B - G_B	105 N
Preload class C - G_C	210 N
Preload class A - G_A	35 N
Fatigue load limit P_u	0.129 kN
Calculation factor f_1	0.97
Calculation factor f_{2C}	1.15
Calculation factor f_{2A}	1
Calculation factor f_{HC}	1

Calculation factor f_{2B}	1.08
Limiting speed for oil lubrication	53000 mm/min
Fatigue load limit - P_u	0.129 kN
Calculation factor - f_1	0.97
Calculation factor - Y_2	1.41
Calculation factor - X_2	0.67
Calculation factor - Y_1	0.92
Calculation factor - Y_0	0.76
Calculation factor - f_{HC}	1
Calculation factor - f_{2A}	1
Calculation factor - f_{2C}	1.15
Calculation factor - f_{2B}	1.08
Limiting speed for grease lubrication	34000 r/min
Basic static load rating C_0	3.05 kN
Static axial stiffness, preload class B	95 N/ μ m
Static axial stiffness, preload class A	60 N/ μ m
Attainable speed for grease lubrication	34000 r/min
Static axial stiffness, preload class C	128 N/ μ m
Basic static load rating - C_0	3 kN
Attainable speed for oil-air lubrication	53000 r/min
Reference grease quantity G_{ref}	0.21 cm ³
Calculation factor (single, tandem) Y_2	0.87
Calculation factor	0.38

(single, tandem) Y_0	
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back- to-back, face-to-face) Y_1	0.92
Calculation factor (back- to-back, face-to-face) Y_2	1.41
Calculation factor (back- to-back, face-to-face) Y_0	0.76
Calculation factor (back- to-back, face-to-face) X_2	0.67