



Bearing No. BT4B 328345/HA1

| | |
|-------------------------------------|-----------------|
| D | 407 mm |
| d | 279.4 mm |
| B | 320 mm |
| T | 288 mm |
| Size (mm) | 407x279.4x320 |
| Width (mm) | 320 |
| Mass bearing | 140 kg |
| Bearing number | BT4B 328345/HA1 |
| Thrust factor K | 1.73 |
| Thrust factor - K | 1.73 |
| Bore Diameter (mm) | 407 |
| Outer Diameter (mm) | 279,4 |
| Calculation factor e | 0.33 |
| r _{1,2} min. | 3.5 mm |
| r _{3,4} min. | 1.5 mm |
| d ₁ ? | 343 mm |
| D ₁ ? | 388 mm |
| Calculation factor - e | 0.33 |
| r _{3,4} - min. | 1.5 mm |
| r _{1,2} - min. | 3.5 mm |
| Design variant/feature | TQI |
| Basic dynamic load rating C | 3580 kN |
| Basic dynamic load rating - C | 3580 kN |
| Calculation factor Y ₂ | 3 |
| Fatigue load limit P _u | 765 kN |
| Calculation factor Y ₁ | 2 |
| Calculation factor Y ₀ | 2 |
| Calculation factor - Y ₀ | 2 |
| Calculation factor - Y | 3 |

| | |
|--|---------|
| | 2 |
| Fatigue load limit - P_u | 765 kN |
| Calculation factor - Y_1 | 2 |
| Basic static load rating C_0 | 9000 kN |
| Basic static load rating - C_0 | 9000 kN |
| Comparative radial load rating C_F | 950 kN |
| Comparative axial load rating C_{Fa} | 159 kN |
| Comparative axial load rating - C_{Fa} | 159 kN |
| Comparative radial load rating - C_F | 950 kN |