



Bearing No. 71807 CD/P4

D	47 mm
d	35 mm
B	7 mm
a	9 mm
Ball - z	26
Size (mm)	47x35x7
Width (mm)	7
Mass bearing	0.028 kg
d _n	39.5 mm
d _n	39.5 mm
D ₁	43.1 mm
d ₁	39.1 mm
d ₂	39.1 mm
D ₁	43.1 mm
d ₂	39.1 mm
d ₁	39.1 mm
Bearing number	71807 CD/P4
Preload class A	32 N/micron
Preload class B	56 N/micron
Preload class C	82 N/micron
G _{ref}	0.28 cm ³
Number of balls z	26
D _a max.	45 mm
d _a min.	37 mm
d _b min.	37 mm
D _b max.	46.2 mm
r _a max.	0.3 mm
r _b max.	0.15 mm
Bore Diameter (mm)	47

Outer Diameter (mm)	35
d_a - min.	37 mm
r_a - max.	0.3 mm
$r_{1,2}$ min.	0.3 mm
Calculation factor f	1.18
D_b - max.	46.2 mm
$r_{3,4}$ min.	0.15 mm
r_b - max.	0.15 mm
D_a - max.	45 mm
Ball - D_w	3.175 mm
d_b - min.	37 mm
Calculation factor - f	1.18
$r_{3,4}$ - min.	0.15 mm
$r_{1,2}$ - min.	0.3 mm
Basic dynamic load rating C	4.62 kN
Ball diameter D_w	3.175 mm
Preload class B G_B	75 N
Preload class A G_A	25 N
Basic dynamic load rating - C	4.6 kN
Preload class C G_C	150 N
Preload class A - G_A	25 N
Preload class C - G_C	150 N
Preload class B - G_B	75 N
Calculation factor f_1	1
Fatigue load limit P_u	0.183 kN
Calculation factor f_0	17
Calculation factor f_{2C}	1.16
Calculation factor f_{2B}	1.09
Calculation factor f_{2A}	1
Calculation factor f_{HC}	1

Calculation factor - f	1
Fatigue load limit - P_u	0.183 kN
Calculation factor - f_0	17
Limiting speed for oil lubrication	43000 mm/min
Calculation factor - f_{2B}	1.09
Calculation factor - f_{2A}	1
Calculation factor - f_{2C}	1.16
Calculation factor - f_{HC}	1
Limiting speed for grease lubrication	28000 r/min
Basic static load rating C_0	4.3 kN
Static axial stiffness, preload class A	32 N/ μ m
Static axial stiffness, preload class B	56 N/ μ m
Static axial stiffness, preload class C	82 N/ μ m
Attainable speed for grease lubrication	28000 r/min
Attainable speed for oil-air lubrication	43000 r/min
Basic static load rating - C_0	4.3 kN
Reference grease quantity G_{ref}	0.28 cm ³