



Bearing No. K28X33X17H

Fw	28 mm
Ew	33 mm
Bc	17 mm
Cr	19.8
Cu	5.10
P/S	S
C0r	33.0
Noun	Bearing
Bore	1.102 Inch 28 Millimeter
Width	0.669 Inch 17 Millimeter
UNSPSC	31171512
Weight	0.018 Kg
Retainer	Yes
Oil lub.	15000
Category	Needle Non Thrust Roller Bearing
Inventory	0.0
Separable	No
Component	Roller Assembly Only
Enclosure	Not Applicable
Closed End	Not Applicable
Grease lub.	10000
Bearing No.	K28X33X17H
Shaft(max.)	28.000
Shaft(min.)	27.991
Weight / LBS	0.04
Housing(max.)	33.025
Housing(min.)	33.009
Inch - Metric	Metric

Product Group	B04144
Self Aligning	No
Other Features	Radial Roller Hardened Steel Cage
Bearing number	K28X33X17H
Keyword String	Needle
Thrust Bearing	No
Rolling Element	Needle Roller Bearing
Outside Diameter	1.299 Inch 33 Millimeter
Long Description	28MM Bore; 33MM Outside Diameter; 17MM Width; Needle Roller Bearing; Roller Assembly Only; No Self Aligning; Retainer; Single Row of Rollers; No Separable
Manufacturer URL	http://www.koyousa.com
(Refer.)Mass(kg)	0.018
Manufacturer Name	KOYO
Weight / Kilogram	0.015
Bore Diameter (mm)	28
Outer Diameter (mm)	33
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.40.00.00
(Oil) Lubrication Speed	15000 r/min
Manufacturer Item Number	K28X33X17H
Number of Rows of Rollers	Single Row
(Grease) Lubrication Speed	10000 r/min
Basic static load rating (C0)	33.0 kN
Basic dynamic load	19.8 kN

rating (C)	
------------	--