



Bearing No. BT1B 328068/HA4

a	254 mm
d	711.2 mm
D	939.8 mm
T	120.65 mm
B	115.3 mm
C	73.25 mm
Size (mm)	939.8x711.2x120.65
Width (mm)	120,65
Mass bearing	206 kg
d ₁	829.431 mm
Limiting speed	480 r/min
Bearing number	BT1B 328068/HA4
Reference speed	340 r/min
D _a max.	908 mm
D _b min.	912 mm
D _a min.	850 mm
d _b min.	743 mm
d _a max.	758 mm
C _a min.	17 mm
C _b min.	47 mm
r _a max.	6 mm
r _b max.	6 mm
Bore Diameter (mm)	939,8
Outer Diameter (mm)	711,2
Calculation factor e	0.75
Calculation factor Y	0.8
r _b - max.	6 mm
r _a - max.	6 mm
C _b - min.	47 mm
C _a - min.	17 mm

D_b - min.	912 mm
D_a - max.	908 mm
$r_{1,2}$ min.	6.4 mm
$r_{3,4}$ min.	6.4 mm
D_a - min.	850 mm
d_b - min.	743 mm
d_a - max.	758 mm
d_1 ?	829.431 mm
$r_{3,4}$ - min.	6.4 mm
$r_{1,2}$ - min.	6.4 mm
Calculation factor - Y	0.8
Calculation factor - e	0.75
Basic dynamic load rating C	2640 kN
Basic dynamic load rating - C	2640 kN
Fatigue load limit P_u	425 kN
Calculation factor Y_0	0.45
Calculation factor - Y_0	0.45
Fatigue load limit - P_u	425 kN
Basic static load rating C_0	6200 kN
Basic static load rating - C_0	6200 kN