



Bearing No. 11162/11300

e	0.49
d	41,275 mm
D	76,2 mm
T	18,009 mm
B	17,384 mm
C	14,288 mm
a	17,4 mm
Da	67 mm
B_	17.384
Db	71 mm
da	49 mm
Y0	0.68
db	46,5 mm
C0	51
D_	76.2
Z_	19
C_	14.288
Y1	1.2
DE_	65.737
SLR	11
D_a	67
DI_	51.246
DA1	7.782
DA2	7.019
CUP	0.129
DA_	7.403
D_b	71
RAr	111.502
SDM_	58.436
KBRG	3161

yobi	11162/11300
CONE	0.212
ALP21	36
ALP22	0
ALP23	0
BETA_	2
BET21	4
BET23	0
BET22	0
r min.	1,5 mm
LangID	1
Weight	0,341 Kg
ALPHA_	18
r1 min.	1,5 mm
ra max.	1,5 mm
Oil rpm	6300
outer r	1.5
hidYobi	11162/11300
GRS rpm	4500
inner r	1.5
hidTable	ecat_NSTPRI
inner ra	1.5
outer rb	1.5
ra1 max.	1,5 mm
Size (mm)	41.275x76.2x18.009
SHOG_yobi	11162R/11300R
Prod_Type3	TRBSR_ID_A
Width (mm)	18,009
Bearing number	11162/11300
Bore Diameter (mm)	41,275
Outer Diameter (mm)	76,2
Calculation factor (e)	0,49

(Oil) Lubrication Speed	6300 r/min
Calculation factor (Y0)	0,68
(Grease) Lubrication Speed	4500 r/min
Basic static load rating (C0)	51 kN
Basic dynamic load rating (C)	42,5 kN