



Bearing No. NKX60Z

a	80,5 mm
k	3 mm
d	60 mm
D	72 mm
C	40 mm
Cr	29.8 kN
C2	12 mm
Lw	15.8 mm
C1	17 mm
Dw	2.5 mm
dw	60 mm
D2	86,5 mm
D1	85 mm
Fw	60 mm
Ca	41.5 kN
C0r	71.5 kN
Dw1	8.73 mm
C0a	113 kN
Mass	0.48 kg
da min	75 mm
rs min	1 mm
r min.	1 mm
Weight	0,484 Kg
ras max	1 mm
ra max.	1 mm
da min.	75 mm
Category	Bearings
Inventory	0.0
Nlim (oil)	3,700 rpm
Nlim (grease)	2,600 rpm

Product Group	B04144
Bearing number	NKX60Z
Precision class	P0
Manufacturer Name	NTN
Weight / Kilogram	0.519
Bore Diameter (mm)	60
Outer Diameter (mm)	86,5
Minimum Buy Quantity	N/A
(Grease) Lubrication Speed	2600 r/min
Static load rating axial (C0)	113 kN
Dynamic load rating axial (C)	41,5 kN
Lubrication hole on outer ring	Oui/Yes
Static load rating radial (C0)	71,5 kN
Dynamic load rating radial (C)	29,8 kN
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C