



Bearing No. K32X38X26H

Fw	32 mm
Ew	39 mm
Bc	26 mm
Cr	33.2
Cu	9.15
P/S	S
C0r	58.8
Noun	Bearing
Bore	1.26 Inch 32 Millimeter
Width	1.024 Inch 26 Millimeter
UNSPSC	31171512
Weight	0.037 Kg
Retainer	Yes
Oil lub.	14000
Category	Needle Non Thrust Roller Bearing
Inventory	0.0
Separable	No
Component	Roller Assembly Only
Enclosure	Not Applicable
Closed End	Not Applicable
Grease lub.	8800
Bearing No.	K32X38X26H
Shaft(max.)	32.000
Shaft(min.)	31.989
Weight / LBS	0.082
Housing(max.)	38.025
Housing(min.)	38.009
Inch - Metric	Metric
Product Group	B04144

Self Aligning	No
Other Features	Radial Roller Hardened Steel Cage
Bearing number	K32X38X26H
Keyword String	Needle
Thrust Bearing	No
Rolling Element	Needle Roller Bearing
Outside Diameter	1.496 Inch 38 Millimeter
Long Description	32MM Bore; 38MM Outside Diameter; 26MM Width; Needle Roller Bearing; Roller Assembly Only; No Self Aligning; Retainer; Single Row of Rollers; No Separable
Manufacturer URL	http://www.koyousa.com
(Refer.)Mass(kg)	0.037
Manufacturer Name	KOYO
Weight / Kilogram	0.039
Bore Diameter (mm)	32
Outer Diameter (mm)	39
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.40.00.00
(Oil) Lubrication Speed	14000 r/min
Manufacturer Item Number	K32X38X26H
Number of Rows of Rollers	Single Row
(Grease) Lubrication Speed	8800 r/min
Basic static load rating (C0)	58.8 kN
Basic dynamic load rating (C)	33.2 kN