



**Bearing No. 33122-N11CA**

|                     |   |
|---------------------|---|
| m                   | 11,4 kg / Weight                        |
| D                   | 180 mm                                  |
| e                   | 0,42                                    |
| A                   | 26 mm                                   |
| d                   | 110 mm                                  |
| 2T                  | 112 mm                                  |
| 2B                  | 112 mm                                  |
| Size (mm)           | 110x180x112                             |
| Width (mm)          | 112                                     |
| $C_r$               | 630000 N / Dynamic load rating (radial) |
| $Y_2$               | 2,4                                     |
| $Y_1$               | 1,61                                    |
| $Y_0$               | 1,58                                    |
| $n_G$               | 3650 1/min                              |
| $n_B$               | 2050 1/min / Reference speed            |
| $C_{ur}$            | 146000 N / Fatigue limit load, radial   |
| $C_{0r}$            | 1260000 N / Static load rating (radial) |
| Bearing number      | 33122-N11CA                             |
| $r_{b \max}$        | 2 mm                                    |
| $D_{a \min}$        | 155 mm                                  |
| $D_{a \max}$        | 170 mm                                  |
| $C_{a \min}$        | 9 mm                                    |
| $d_{a \max}$        | 121 mm                                  |
| Bore Diameter (mm)  | 110                                     |
| Outer Diameter (mm) | 180                                     |
| $r_{3, 4 \min}$     | 2 mm                                    |

