



Bearing No. 33213JR

| | |
|---------|----------------------------|
| D | 120 mm |
| d | 65 mm |
| T | 41 mm |
| B | 41 mm |
| C | 32 mm |
| a | 30 mm |
| e | 0.39 |
| Cr | 250 |
| Y0 | 0.85 |
| Y1 | 1.54 |
| Cu | 43.0 |
| C0r | 277 |
| Bore | 2.559 Inch 65 Millimeter |
| Noun | Bearing |
| a(mm) | 30.0 |
| Da min | 102 mm |
| da max | 74 mm |
| Weight | 2,02 Kg |
| r min. | 2 mm |
| r(min) | 2 |
| UNSPSC | 31171516 |
| Db(min) | 115 |
| db(max) | 74 |
| Da(max) | 110 |
| Da(min) | 102 |
| r1(min) | 1.5 |
| Sa(min) | 7 |
| Sb(min) | 9 |
| ra(max) | 2 |
| | |

| | |
|------------------|--|
| rb(max) | 1.5 |
| da(min) | 75 |
| ra max. | 2 mm |
| Db min. | 115 mm |
| Da max. | 110 mm |
| da min. | 75 mm |
| r2 min. | 1,5 mm |
| rb max. | 1,5 mm |
| Oil lub. | 4300 |
| Category | Tapered Roller Bearings Assembly |
| Size (mm) | 65x120x41 |
| Component | Assembly |
| Inventory | 0.0 |
| Width (mm) | 41 |
| Grease lub. | 3200 |
| Bearing No. | 33213JR |
| Basic Number | 33213 |
| Weight / LBS | 4.453 |
| Inch - Metric | Metric |
| Product Group | B04334 |
| Other Features | High Load Capacity |
| Keyword String | Tapered |
| Assembly Width | 1.614 Inch 41 Millimeter |
| Bearing number | 33213JR |
| Precision Class | Standard |
| (Refer.)Mass(kg) | 2.02 |
| Outside Diameter | 4.724 Inch 120 Millimeter |
| Manufacturer URL | http://www.koyousa.com |
| Long Description | Assembly; Standard Precision; 65MM Bore; 120MM Outside |

| | |
|----------------------------------|--|
| | Diameter; 41MM Assembly Width; Single Row of Rollers |
| Weight / Kilogram | 2.02 |
| Manufacturer Name | KOYO |
| Bore Diameter (mm) | 65 |
| Outer Diameter (mm) | 120 |
| Minimum Buy Quantity | N/A |
| Calculation factor (e) | 0,39 |
| Number of Tapered Rows | Single Row |
| Harmonized Tariff Code | 8482.20.00.00 |
| Flange Outside Diameter | 0 Inch 0 Millimeter |
| (Oil) Lubrication Speed | 4300 r/min |
| Calculation factor (Y0) | 0,85 |
| Manufacturer Item Number | 33213JR |
| (Grease) Lubrication Speed | 3200 r/min |
| Basic static load rating (C0) | 277 kN |
| Basic dynamic load rating (C) | 200 kN |