



Bearing No. 62/22ZZ

| | |
|------|-------------------------------|
| D | 50 mm |
| d | 22 mm |
| B | 14 mm |
| C | 14 mm |
| r | 1 |
| Z_ | 8 |
| B_ | 14 |
| D_ | 50 |
| ra | 1 |
| C0 | 6.8 |
| fo | 13.5 |
| DI_ | 28.562 |
| SRI | 4.01 |
| D_a | 45 |
| DE_ | 44.438 |
| DA_ | 7.938 |
| SRE | 4.21 |
| SRIN | 0 |
| SBRG | 2 |
| yobi | 62/22ZZ |
| SDM_ | 36.5 |
| SREX | 0.04 |
| KBRG | 6141 |
| bomp | 0 |
| mass | 0.119 |
| SRIX | 0.02 |
| Bore | 0.866 Inch 22 Millimeter |
| SREN | 0 |
| Noun | Bearing |
| | |

| | |
|------------------|-------------------------------|
| ALPHA_ | 0 |
| da min | 27 |
| LangID | 1 |
| r min. | 1 mm |
| UNSPSC | 31171504 |
| da max | 29,5 mm |
| C_conv | 12900 |
| Weight | 0,119 Kg |
| ra max. | 1 mm |
| hidYobi | 62/22ZZ |
| GRS rpm | 14000 |
| Da max. | 45 mm |
| da min. | 27 mm |
| Category | Single Row Ball Bearing |
| hidTable | ecat_NSRDGB |
| Snap Ring | No |
| Size (mm) | 22x50x14 |
| Enclosure | 2 Metal Shields |
| Inventory | 0.0 |
| Width (mm) | 14 |
| Prod_Type3 | DGBB_SR_ZZ |
| Weight / LBS | 0.2624 |
| Cage Material | Steel |
| Inch - Metric | Metric |
| Product Group | B00308 |
| Bearing number | 62/22ZZ |
| Keyword String | Ball |
| Other Features | Deep Groove |
| Precision Class | ABEC 1 ISO P0 |
| Rolling Element | Ball Bearing |
| Outer Race Width | 0.551 Inch 14 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |

| | |
|---------------------------------|--|
| Long Description | 22MM Bore; 50MM Outside Diameter; 14MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stee |
| Manufacturer URL | http://www.nskamericas.com |
| Outside Diameter | 1.969 Inch 50 Millimeter |
| Weight / Kilogram | 0.118 |
| Manufacturer Name | NSK |
| Internal Clearance | C0-Medium |
| Bore Diameter (mm) | 22 |
| Outer Diameter (mm) | 50 |
| Minimum Buy Quantity | N/A |
| Harmonized Tariff Code | 8482.10.50.68 |
| Internal Special Features | No |
| (Grease) Lubrication Speed | 14 000 r/min |
| Basic static load rating (C0) | 6,8 kN |
| Basic dynamic load rating (C) | 12,9 kN |
| Maximum Capacity / Filling Slot | No |