



Bearing No. 33215JR

D	130 mm
d	75 mm
T	41 mm
B	41 mm
C	31 mm
a	32,5 mm
e	0.43
Cr	266
Cu	47.7
Y0	0.77
Y1	1.40
C0r	310
Bore	2.953 Inch 75 Millimeter
Noun	Bearing
a(mm)	32.5
Da min	111 mm
da max	83 mm
Weight	2,26 Kg
r min.	2 mm
r(min)	2
UNSPSC	31171516
Db(min)	125
db(max)	83
Da(max)	121.5
Da(min)	111
r1(min)	1.5
Sa(min)	7
Sb(min)	10
ra(max)	2

rb(max)	1.5
da(min)	85
ra max.	2 mm
Db min.	125 mm
Da max.	121,5 mm
da min.	85 mm
r2 min.	1,5 mm
rb max.	1,5 mm
Oil lub.	3900
Category	Tapered Roller Bearings Assembly
Size (mm)	75x130x41
Component	Assembly
Inventory	0.0
Width (mm)	41
Grease lub.	2900
Bearing No.	33215JR
Basic Number	33215
Weight / LBS	4.982
Inch - Metric	Metric
Product Group	B04334
Other Features	High Load Capacity
Keyword String	Tapered
Assembly Width	1.614 Inch 41 Millimeter
Bearing number	33215JR
Precision Class	Standard
(Refer.)Mass(kg)	2.26
Outside Diameter	5.118 Inch 130 Millimeter
Manufacturer URL	http://www.koyousa.com
Long Description	Assembly; Standard Precision; 75MM Bore; 130MM Outside

	Diameter; 41MM Assembly Width; Single Row of Rollers
Weight / Kilogram	2.26
Manufacturer Name	KOYO
Bore Diameter (mm)	75
Outer Diameter (mm)	130
Minimum Buy Quantity	N/A
Calculation factor (e)	0,43
Number of Tapered Rows	Single Row
Harmonized Tariff Code	8482.20.00.00
Flange Outside Diameter	0 Inch 0 Millimeter
(Oil) Lubrication Speed	3900 r/min
Calculation factor (Y0)	0,77
Manufacturer Item Number	33215JR
(Grease) Lubrication Speed	2900 r/min
Basic static load rating (C0)	310 kN
Basic dynamic load rating (C)	212 kN